

ASSA ABLOY SAFETY DATA SHEET

PYROPANEL ADFACON ADHESIVE

Infosafe No.: LQBHD ISSUED Date : 09/11/2022 ISSUED by: ASSA ABLOY AUSTRALIA PTY LTD

Section 1 - Identification

Product Identifier PYROPANEL ADFACON ADHESIVE

Company Name ASSA ABLOY AUSTRALIA PTY LTD (ABN 90 086 451 907)

Address 235 Huntingdale Road Oakleigh VIC 3166 Australia

Telephone/Fax Number Tel: 03 9837 8500

Emergency Phone Number +613 9837 8500 (24 hours)

E-mail Address sales@pyropanel.com.au

Recommended use of the chemical and restrictions on use Sprayable solvent contact adhesive.

Illicit Drug Precursors

This product contains Category III: Illicit Drug Reagent/Essential Chemicals in the Code of Practice for Supply Diversion into Illicit Drug Manufacture.

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia. Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Flammable liquids: Category 2 Skin corrosion/irritation: Category 2 Eye damage/irritation: Category 2A Reproductive toxicity: Category 1A Specific target organ toxicity (single exposure): Category 3 (Narcotic) Specific target organ toxicity (repeated exposure): Category 2 Aspiration hazard: Category 1 Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2 Signal Word (s)

DANGER

Hazard Statement (s)

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Page 1 / 10

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)

Health hazard, Exclamation mark, Flame, Environment



Precautionary Statement – Prevention

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Precautionary Statement – Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P332+P313 If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P331 Do NOT induce vomiting.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder) to extinguish. P391 Collect spillage.

Precautionary Statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Precautionary Statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

Other Information

This product contains an Ototoxic substance.

Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 3 - Composition and Information on Ingredients

Name	CAS	Proportion		
Solvent naphtha, petroleum, light aliphatic	64742-89-8	30-60 %		
Toluene	108-88-3	10-30 %		
Acetone	67-64-1	10-30 %		
n-hexane	110-54-3	<10 %		
Ingredients determined not to be hazardous		Balance		

Ingredients

Section 4 - First Aid Measures

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

Section 5 - Firefighting Measures

Suitable Extinguishing Media

Use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific hazards arising from the chemical

Highly flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

•3YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

Section 6 - Accidental Release Measures

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a wellventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, foodstuffs, clothing and incompatible materials such as oxidising agents. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Toluene: TWA: 50 ppm, 191 mg/m³ STEL: 150 ppm, 574 mg/m³ Note: Sk

Acetone: TWA: 500 ppm, 1185 mg/m³ STEL: 1000 ppm, 2375 mg/m³

n-Hexane: TWA: 20 ppm; 72 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eighthour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at

any time during a normal eight-hour workday. 'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur. Source: Safe Work Australia

Biological Monitoring

Name: Toluene Determinant: Toluene in blood Value: 0.02 mg/L Sampling time: Prior to last shift of workweek Notation: -Determinant: Toluene in urine Value: 0.03 mg/L Sampling time: End of shift Notation: -Determinant: o-Cresol in urine Value: 0.3 mg/g creatinine Sampling time: End of shift Notation: B Source: American Conference of Industrial Hygienists (ACGIH).

Name: Acetone Determinant: Acetone in urine Value: 25 mg/L Sampling time: End of shift Source: American Conference of Industrial Hygienists (ACGIH).

Name: n-hexane Determinant: 2,5-Hexanedione in urine** Value: 0.5 mg/l Sampling time: End of shift. **without hydrolysis Source: American Conference of Industrial Hygienists (ACGIH).

Control Banding Not available

Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye and Face Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/ face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as Nitrile rubber. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Thermal Hazards

No further relevant information available.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Properties	Description	Properties	Description
Form	Liquid	Appearance	Yellow or Red liquid
Colour	Yellow or Red	Odour	Typical hydrocarbon liquid
Melting Point	Not available	Boiling Point	56 - 115°C
Decomposition Temperature	Not available	Solubility in Water	Immiscible in water
Specific Gravity	Approximately 0.81 g/cm ³	рН	Not applicable
Vapour Pressure	Not available	Relative Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Volatile Component	Not available
Partition Coefficient: n- octanol/water (log value)	Not available	Density	Not available
Flash Point	< -20 °C	Flammability	Highly flammable
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available	Explosion Properties	Not available
Oxidising Properties	Not available	Particle Size	Not available

Section 9 - Physical and Chemical Properties

Section 10 - Stability and Reactivity

Reactivity

React with incompatible materials.

Chemical Stability

Stable under normal conditions of handling and storage.

Possibility of hazardous reactions

Not available.

Conditions to Avoid

Heat, direct sunlight, open flames, high temperatures or other sources of ignition.

Incompatible Materials

Oxidising agents.

Hazardous Decomposition Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information

Toxicology Information Toxicity data for material given below.

Acute Toxicity - Oral

Based on ingredients: LD50 > 2,000 mg/Kg bw

Acute Toxicity - Dermal

Based on ingredients: LD50 > 2,000 mg/Kg bw

Acute Toxicity - Inhalation

Based on ingredients: LC50 > 20.0 mg/L for vapours LC50 > 5.0 mg/L for dust and mist

Ingestion

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, oesophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

Inhalation

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory Sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ Cell Mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard. Toluene and Mineral oils are listed as Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

May damage fertility or the unborn child. Classified as a Known or presumed human reproductive or developmental toxicant.

STOT - Single Exposure

May cause drowsiness or dizziness.

STOT - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Other Information

This product contains an Ototoxic substance. Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 12 - Ecological Information

Ecotoxicity

Toxic to aquatic life with long lasting effects. Acute toxicity estimate (based on ingredients): > 100 mg/L.

Persistence and degradability

BCF = 500 and/or log Kow = 4

Mobility

Not available

Bioaccumulative Potential Not available

Other Adverse Effects Not available

Environmental Protection Do not discharge this material into waterways, drains and sewers.

Hazardous to the Ozone Layer

This product is not expected to deplete the ozone layer.

Section 13 - Disposal Considerations

Disposal Considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not cut, puncture or weld on or near containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. To minimise personal exposure to the chemical, refer to Section 8-Exposure controls and personal protection.

Section 14 - Transport Information

Transport Information

Road and Rail Transport (ADG7):

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

- Class 3 Flammable Liquids are incompatible in a placard load with any of the following:
- Class 1, Explosives
- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with
- a capacity individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising Agents and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7: Radioactive materials unless specifically exempted

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1133

Proper Shipping Name: ADHESIVES (n-Hexane & Solvent naphtha, petroleum, light aliphatic MARINE POLLUTANT)

Class/Division: 3 Packing Group: II EMS: F-E,S-D

Special Provisions: none

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. UN No: 1133 **Proper Shipping Name: ADHESIVES** Class/Division: 3 Packing Group: II Packaging Instructions (passenger & cargo): 353 Packaging Instructions (cargo only): 364

Hazard Label: Flammable liquid Special Provisions: A3

ADG U.N. Number 1133

ADG Proper Shipping Name ADHESIVES

ADG Transport Hazard Class 3

ADG Packing Group

Hazchem Code •3YE

IERG Number 14

Special Precautions for User Not available

IMDG Marine pollutant Yes

Transport in Bulk Not available

Section 15 - Regulatory Information

Regulatory Information

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

S5

Montreal Protocol Not listed

Stockholm Convention Not listed

Rotterdam Convention Not listed

International Convention for the Prevention of Pollution from Ships (MARPOL) Not available

Agricultural and Veterinary Chemicals Act 1994 Not available

Basel Convention Not available

Section 16 - Any Other Relevant Information

Date of Preparation

SDS created: November 2022

Version Number

1.0

Literature References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice. Standard for the Uniform Scheduling of Medicines and Poisons. Australian Code for the Transport of Dangerous Goods by Road & Rail.

Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Code of Practice for Supply Diversion into Illicit Drug Manufacture.

National Code of Practice for Chemicals of Security Concern.

Agricultural Compounds and Veterinary Chemicals Act.

International Agency for Research on Cancer (IARC) Monographs.

Montreal Protocol on Substances that Deplete the Ozone Layer.

Stockholm Convention on Persistent Organic Pollutants (POPs).

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.

International Air Transport Association (IATA) Dangerous Goods Regulations.

International Maritime Dangerous Goods (IMDG) Code.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals (7th revised edition).

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.